



with independent sideshift - Fork length max. 1.300 mm - 2 hydraulic functions

Technical Data

Model	Cap. on forks kg	Cap. as clamp kg	LCD mm	S mm	A mm	B mm	D mm	E mm	G mm	A1 mm	J mm	ISO	V mm	CofG Z mm	Weight kg	Price €	Add-on price for fork length 1.300 mm €
1T411D	1.500	700	500	±100	310-1.490	970	40	100	1.200	580-1.760	110	2	248	245	331	On request	On request
1,5T411D	2.000	1.250	500	±100	110-1.110	970	40	120	1.200	400-1.400	110	2	248	267	343	On request	On request
1,5T411D	2.000	1.250	500	±100	290-1.470	970	40	120	1.200	580-1.760	110	2	248	263	353	On request	On request
1,5T411D	2.000	1.250	500	±100	300-1.650	1.130	40	120	1.200	590-1.940	110	2	248	257	364	On request	On request
1,5T411D	2.000	1.250	500	±100	280-1.680	1.200	40	120	1.200	570-1.970	110	2	248	254	369	On request	On request
2T411D	2.800	2.000	500	±100	220-1.420	1.040	50	150	1.200	570-1.770	110	2	258	305	450	On request	On request
2T411D	2.800	2.000	500	±100	130-1.330	1.130	50	150	1.200	480-1.680	110	2	258	302	456	On request	On request
2T411D	2.800	2.000	500	±100	230-1.530	1.130	50	150	1.200	580-1.880	110	2	258	301	458	On request	On request
2T411D	2.800	2.000	500	±100	230-1.730	1.330	50	150	1.200	580-2.080	110	2	258	294	473	On request	On request
2T411D	2.800	2.000	500	±100	220-1.420	1.040	50	150	1.200	570-1.770	110	3	258	305	450	On request	On request
2T411D	2.800	2.000	500	±100	130-1.330	1.130	50	150	1.200	480-1.680	110	3	258	302	456	On request	On request
2T411D	2.800	2.000	500	±100	230-1.530	1.130	50	150	1.200	580-1.880	110	3	258	301	458	On request	On request
2T411D	2.800	2.000	500	±100	230-1.730	1.330	50	150	1.200	580-2.080	110	3	258	294	473	On request	On request
3T411D	3.600	2.500	500	±100	225-1.525	1.130	60	150	1.200	605-1.905	110	3	267	287	573	On request	On request
3T411D	3.600	2.500	500	±100	225-1.855	1.460	60	150	1.200	605-2.235	110	3	267	276	604	On request	On request

Hydraulically turnable forks available upon request.
 Slip-on arms for the forks model T103A and T103AG
 Also available without sideshift, model T401D
 Load Backrest see model T179.
 Fork length max. 1.300 mm



Specification:

Flexibility is the motto of the KAUP Fork Clamp with Turnable Forks T411D. This clamp is a very universally applicable attachment, because the carrying part of the hook-on forks is turnable by $\pm 90^\circ$. Therefore, the rotary hook-on fork clamp can be used for hook-on fork works as well as the clamps by bale, boxes and cardboards. If the carrying part are turned only around by 45° , besides, the transport of barrels or other cylindrical bodies is easily possible.

Qualities:

- Suitably to the Handling of the most different load forms - palettised product, grid boxing, underrun loads (basic position), barrels and cylindrical bodies (45 ° positions), bales, clamps, cardboards etc. (90 ° positions)
- Very good visibility conditions
- Independent sideshift serially
- Load backrest optionally
- Puttable on clamp arms optionally