



with independent sideshift - 2 hydraulic functions

Technical Data

| Model | Cap. kg | LCD mm | S mm | A mm | B mm | C mm | H mm | I mm | K mm | ISO | Md Δ -P = 125 bar Nm | Req. oil volume per rotation ltr. | V mm | CofG Z mm | Weight kg | Price € |
|-----------|------------|-----------|---------|---------|---------|---------|---------|---------|---------|-----|--------------------------------|--------------------------------------|---------|-----------------|--------------|------------|
| 1T391.2 | 1.800 | 500 | ±100 | 780 | 780 | 858 | 213 | 294 | 32 | 2 | 6.013 | 7,6 | 192 | 99 | 199 | On request |
| 1T391.2 | 1.800 | 500 | ±100 | 780 | 890 | 858 | 213 | 294 | 32 | 2 | 6.013 | 7,6 | 192 | 101 | 205 | On request |
| 2T391.1 | 2.500 | 500 | ±100 | 790 | 1.040 | 858 | 269 | 492 | 32 | 2 | 7.700 | 9,7 | 172 | 90 | 255 | On request |
| 2T391.2 | 2.500 | 500 | ±100 | 1.000 | 1.040 | 950 | 270 | 345 | 32 | 2 | 7.700 | 9,7 | 208 | 104 | 283 | On request |
| 2,5T391.1 | 3.200 | 500 | ±100 | 790 | 1.100 | 850 | 269 | 492 | 40 | 3 | 7.700 | 9,7 | 198 | 113 | 310 | On request |
| 2,5T391.2 | 3.200 | 500 | ±100 | 1.000 | 1.100 | 1.043 | 270 | 345 | 40 | 3 | 7.700 | 9,7 | 208 | 110 | 350 | On request |
| 4T391.2 | 5.000 | 500 | ±100 | 1.010 | 1.100 | 1.010 | 339 | 395 | 40 | 3 | 8.950 | 11,3 | 215 | 113 | 425 | On request |
| 4,5T391.1 | 5.000 | 500 | ±160 | 1.110 | 1.350 | 940 | 378 | 675 | 49 | 4 | 14.823 | 17,4 | 229 | 123 | 595 | On request |
| 5T391.2 | 6.000 | 600 | ±160 | 1.260 | 1.350 | 1.260 | 345 | 455 | 50 | 4 | 13.434 | 15,7 | 264 | 142 | 740 | On request |
| 6T391.2 | 6.500 | 600 | ±160 | 1.260 | 1.350 | 1.260 | 345 | 455 | 50 | 4 | 17.157 | 20,7 | 264 | 138 | 790 | On request |
| 8T391.2 | 8.000 | 900 | ±160 | 1.300 | 1.600 | 1.700 | 396 | 480 | 54 | 4 | 21.679 | 18,8 | 304 | 164 | 1.110 | On request |

Rotators with higher rotating speeds available upon request

Other fork carriage widths available upon request.

Lateral supporting fork 1.000 mm (add-on-price)

Lateral supporting fork 1.000 mm (add-on-price)

Downhold T167 to empty metal grid boxes etc on request

Matching forks for KAUP-Rotators on request.

When forks are used in combination with a Rotator extremely high strain is applied to the lower fork angle when rotating a load which in turn strains the lower brackets.

For this type of operation KAUP recommends forks with strengthened lower brackets. Strengthened lower brackets can be ordered for all ISO forks model T180.



Specification:

As opposed to the entrance models of the rotating attachments the KAUP Rotator 360° endless T391 owns a sideshift. It allows an even more exact work with the device.

According to application case and customer wish the gear can be positioned at two different places. Differing lost loads and residual capacities are the results.

Qualities:

- Good visibility conditions
- Good residual capacity

- Rotation 360° endlessly
- Robust construction with gear drive
- Sideshift serially
- Original forks usable
- Lateral supporting fork and load stabilizers optionally