



Quick mounting - hook-on type QUICKSEAL cylinders, bottom mounting brackets with EASYSLIDE greasable sliding pads, Max. width 1.190 mm, 1 hydraulic function

### Technical Data

Model	Cap. kg	LCD mm	B mm	A mm	C mm	D mm	S mm	ISO	V mm	CofG Z mm	Weight kg	Price €
2T151P4N	2.500	500	890	550	33	28	±100	2	55	20	51	On request
2T151P4N	2.500	500	920	590	33	28	±100	2	55	20	52	On request
2T151P4N	2.500	500	980	590	33	28	±100	2	55	20	54	On request
2T151P4N	2.500	500	1.000	590	33	28	±100	2	55	20	54	On request
2T151P4N	2.500	500	1.020	590	33	28	±100	2	55	20	55	On request
2T151P4N	<b>2.500</b>	<b>500</b>	<b>1.040</b>	<b>590</b>	<b>33</b>	<b>28</b>	<b>±100</b>	<b>2</b>	<b>55</b>	<b>20</b>	<b>56</b>	<b>On request</b>
2T151P4N	2.500	500	1.100	590	33	28	±100	2	55	20	57	On request
2T151P4N	2.500	500	1.150	590	33	28	±100	2	55	20	58	On request

Load Backrest see model T179.

When using forks longer than 1.600 mm we recommend the high performance model 2T151P2.



## Specification:

The 2T151P4N Sideshifter is the gateway to the KAUP Sideshifter program. This attachment with very good visibility is the right choice when palletised goods must be shifted laterally on a regular basis. The Sideshifter optimises in-plant material handling.

## Qualities:

- Highest possible residual capacity due to low weight and minimum lost load centre
- Most favourable lost load centre of all hook-on sideshifters currently available
- Maximum visibility - very slim S-profiles form the fork carriage